

DATASHEET TRASSIR MiniNVR Compact



TRASSIR MiniNVR Compact is a network video recorder for building CCTV systems. Up to 16 channels are available for record, playback and display.



Rear panel:

- 1. 12V DC power input
- 2. Network interface
- 3 USB 3.0 interface
- 4. USB 2.0 interfaces

- 5. HDMI interface
- 6. D-SUB interface
- 7. Audio input/output
- 8. Power button

Specification:

Operating system	TRASSIR OS (based on Linux)		
IP video input ¹	4/9/16 ch (any models²)		
Resolution of cameras ³	Up to 8MP (depending on camera model ²)		
Bitrate	Up to 256Mb/s		
Video compression	H.265+, H.265, H.264, MPEG4 or MJPEG (depending on camera model ²)		
Network interfaces	1 Ethernet 10/100/1000 Mb/s		
USB interfaces	2 USB 2.0 and 1 USB 3.0		
Maximum internal storage	Up to 1xHDD (3.5")		
Video output⁴	1 D-SUB		
	1 HDMI		
Maximum video	D-SUB / HDMI: FullHD		
output resolution			
Audio inputs/outputs	In: 1 jack 3.5mm		
	Out: 1 jack 3.5mm		
Dimensions, mm	300 x 191.8 x 44.5		
Power supply	12V DC, 5A		
Power consumption	Up to 30W (without HDD)		
Working temperature	045°C		
Package size, mm	524 x 80 x 274		

¹Depending on NVR model.

Basic equipment:

Network Video Recorder	1 pcs.
Power Supply 12V (5A)	1 pcs.
• Mouse	1 pcs.
Datasheet for server	1 pcs.

Warranty service:

• Specify the information about the warranty on www.trassir.com.

DATE OF PRODUCTION	 SERIAL NUMBER
KEY NUMBER	

² You can find list of per-integrated cameras on www.trassir.com

³ Enable hardware acceleration in TRASSIR to view the video in the resolution of 8 megapixels.

⁴ The NVR can be connected to two independent displays.